

QUICKSPECS

Compaq P710 CRT
Monitor

MODELS

Compaq P710 CRT Monitor
210189-001

Note: AssetControl monitor. AssetControl features are accessible with Compaq desktops featuring Intelligent Manageability

SPECIFICATIONS

Compaq P710 CRT Monitor

Type	Colour auto- scanning with Digital Control
Picture Tube (diagonal)	17 in Diamondtron NF CRT
Viewable (diagonal)	16 in (41 cm)
Pitch	0.25 mm Aperture Grille Pitch
Graphic Preset Modes	1600 x 1200 1280 x 1024 1024 x 768 800 x 600
Note: All modes are non-interlaced unless specified otherwise. V Frequency shown Maximum / Presets	76 Hz/75 Hz, 85 Hz/75 Hz, 115 Hz/75 Hz, 130 Hz/75 Hz, 85 Hz 85 Hz 85 Hz 85 Hz
	640 x 480
	130 Hz/60 Hz, 85 Hz
Text Mode	720 x 400 70 Hz
Mac Compatible Modes	1152 x 870 75 Hz
Note: Adapter required.	
User-Programmable Modes	11 (5 Pre-set Modes and 6 Pre-loads)
Anti-Glare/Anti-Reflection/Anti-Static	Yes/Yes/Yes
Plug and Play	Yes
Plug and Play Protocol	DDC1/2B
Dual Video Inputs	No
Approvals/Certifications	
MPR-II (Low Emissions)	Yes
TCO-99	Yes
Energy Star Compliant	Yes
UL Listing	Yes
ISO9241-3 VOT Guidelines Approval	Yes
FCC Approval	Yes
CE Marketing (including PFC)	Yes (European assemblies only)
GS Marketing	Yes
Analog Controls	No
Brightness, Contrast	Yes
On-Screen Controls	Yes
Language Selection	
English	Yes
Spanish	Yes
French	Yes
German	Yes
Dutch	No
Italian	No
Japanese	Yes

SPECIFICATIONS *(continued)*

Compaq P710 CRT Monitor *(continued)*

Note: AssetControl monitor. AssetControl features are accessible with Compaq desktops featuring Intelligent Manageability.

User Controls

Sizing and Positioning	Yes
Pincushion	Yes
Pincushion Balance	Yes
Trapezoid	Yes
Tilt (rotation)	Yes
Colour temperature	Yes
Degauss	Yes
Parallelogram	Yes
Individual colour control	No
Zoom	No
Moiré Cancellation	Yes
Convergence	No
Factory Reset	Yes
Corner Purity Adjustment	No

AssetControl

Note: When used with Compaq Intelligent Manageability CPUs and appropriate network software.

Pixel Clock Frequency (Maximum)	208 MHz (1600x1200, 76 Hz, 95 kHz)
Input Impedance	75 ohms
Horizontal Frequency	30 to 96 kHz
Vertical Frequency	50 to 130 Hz
Power Supply	90 to 260 VAC (200-260 VAC for Europe)
Maximum Power Rating	95 W
USB Capabilities	No
Synch Input	Separate H, V sync.
Signal Cable	Detachable 15-in D-sub to 15-pin D-sub cable. D-sub connector on monitor
Maximum Phosphorus Size	32.5 cm x 24.4 cm (40.6 cm diagonal)
Dimensions (HxWxD)	16.2 in x 16.1 in x 17.1 in / 41.3 cm x 41.0 cm x 43.5 cm
Weight	38.6 lbs / 17.5 kg
Temperature	
Operating	50° to 95°F / 10° to 35°C
Non-operating	-4° to 140°F / -20° to 60°C
Humidity	
Operating	20% to 80%
Non-operating	10% to 90%
Warranty	Three-year parts, Three-year on-site labour, or Next Business Day direct replacement

Note: Certain restrictions and exclusions apply. Consult the Compaq Customer Support Centre for details. In Canada, consult the Product Information Centre at 1-888-88-COMPAQ

COMPATIBILITY

Graphics Controllers

3Dlabs Oxygen GVX1
ATI Rage Pro
ATI Mobility P
ATI Rage Pro Turbo 2X
Diamond Viper V730
Diamond Viper V770 Ultra
ELSA GLoria II
ELSA Synergy II
Matrox Millennium II
Matrox Millennium G100 (AGP)
Matrox Millennium G200 (PCI)
Matrox Millennium G400
Matrox Millennium G450 (AGP and PCI)
NVIDIA GeForce 2 GTS
NVIDIA GeForce 256
NVIDIA TNT2 M64
NVIDIA TNT2 Pro
NVIDIA Vanta
Rage ATI Iic
S3 VIRGE/MX (AGP)
Velocity 4000

Chipsets

Intel 810
Intel 810e
Intel 815
Intel 815e
Intel 820
Intel 840

©2000 Compaq Canada Inc. All rights reserved. Compaq is a trademark of Compaq Computer Corporation. The information in this publication is subject to change without notice. Printed in Canada.