

QUICKSPECS

Compaq V700 Monitors

MODELS

V700 Color¹ Monitor
325800-001 (opal)

SPECIFICATIONS

V700 Color¹ Monitor

Type	Color multi-scan with Invar Shadow Mask			
Picture Tube (diagonal)	17-in High-contrast Flat Square CRT			
Viewable (diagonal)	16 in			
Horizontal Dot Pitch	0.22 mm			
Dot Pitch (diagonal)	0.26 mm			
Max Refresh/Preset Graphic Modes²	1800 x 1440 —	1600 x 1200 68 Hz/65 Hz	1280 x 1024 80 Hz/75 Hz	1152 x 864 —
	1024 x 768 105 Hz/75 and 85 Hz	800 x 600 134 Hz/75 and 85 Hz	640 x 480 160 Hz/60, 75, and 85 Hz	640 x 350 160 Hz/ N/A
Text Mode	720 x 400 70 Hz			
Mac Compatible Modes³	1152 x 870 75 Hz	832 x 624 74.5 Hz		
User-Programmable/Preset Graphic Modes	5/10			
Anti-Glare/Anti-Static	Yes/Yes			
Plug and Play	Yes			
Agency Approvals/Certifications				
UL Approval	Yes			
ISO9241-3 VOT Guidelines Approval	Yes			
MPR-II Compliant	Yes			
FCC Approval	Yes			
Energy Star Compliant	Yes			
TCO 99 Compliant	Yes			
On-Screen Controls	Yes			
Language Selection				
English	Yes			
German	Yes			
French	Yes			
Spanish	Yes			
Italian	Yes			
Dutch	Yes			
Portuguese	Yes			
Russian	Yes			
Korean	Yes			
Tilt Base (up/down)	10° up, 5° down			
Swivel	± 90° of center			
User Controls				
Brightness, Contrast	Yes/Yes			
Size and Positioning	Yes			
Pincushion (barrel)	Yes			
Trapezoid	Yes			
Tilt (rotation)	Yes			
Color temperature	Yes			
Parallelogram	Yes			
Pincushion Balance	No			
Individual color control	No			
Moiré Cancellation	Yes			
Convergence	No			
Overscan	No			
Serial Number Display	Yes			
Power Saver (on/off)	Yes			
Display Mode	No			
Degauss	Yes			
Factory Reset	Yes			
Intelligent Manageability				
AssetControl ⁴	Yes			
USB Capabilities	No			



SPECIFICATIONS *(continued)*

V700 Color¹ Monitor *(continued)*

Horizontal Frequency	30 to 85 kHz
Vertical Frequency	50 to 160 Hz
Power Supply ALS	100 to 240 VAC Universal/Auto Switching 50/60 Hz
Maximum Power Rating	< 115 Watts
Power Consumption	< 15W/< 8W
Synch Input	TTL Separate Synch
Signal Cable	15-pin VGA D-sub
Dimensions (HxWxD)	17.49 x 16.7 x 16.98 in/ 44.4 x 42.4 x 43.1 cm
Weight	40 lbs/18.5 kg
Operating Temperature	50° to 95°F/10° to 35°C
Operating Humidity (non-condensing)	20% to 80%
48 Hour Direct Replacement ⁵	If this monitor fails during the parts warranty, Compaq guarantees that a new or like-new monitor replacement will be delivered within 48 hours.
Limited Warranty ⁵	Three-year parts, first-year labor on-site

COMPATIBILITY

Portables

Compaq Armada M300
Compaq Armada M700
Compaq Armada E500
Compaq Armada E700
Compaq Armada V300
Compaq Armada 7800
Compaq Armada 7400
Compaq Armada 6500
Compaq Armada 3500
Compaq Armada 1750
Compaq Armada 1700
Compaq Armada 1500c

Desktops

Compaq Deskpro EN Series Desktop
Compaq Deskpro EN Series Minitower
Compaq Deskpro EN Series Small Form Factor
Compaq Deskpro EP Series

Workstations

Compaq Professional Workstation XP1000
Compaq Professional Workstation AP500

Servers

Compaq ProLiant 7000 Xeon™
Compaq ProLiant 6500 Xeon
Compaq ProLiant 6000 Xeon
Compaq ProLiant 5500 Xeon
Compaq ProLiant 3000 Pentium® III
Compaq ProLiant 3000 6/450
Compaq ProLiant 1600 6/500
Compaq ProLiant 1600 (100 MHz)
Compaq ProLiant 800 (500 MHz)
Compaq Prosignia 720

1. AssetControl monitor. AssetControl features are accessible with Compaq desktops featuring Intelligent Manageability.
2. All modes are non-interlaced unless specified otherwise.
3. Adapter required.
4. When used with Compaq Intelligent Manageability CPUs and appropriate network software.
5. Certain restrictions and exclusions apply. Consult the Compaq Customer Service Support Center for details. In Canada, consult the Product Information Center at 1-800-567-1616 for details.

Compaq, registered United States Patent and Trademark Office.

Other product names mentioned herein may be trademarks and/or registered trademarks of their respective companies.

©1999 Compaq Computer Corporation. All rights reserved. The information in this publication is subject to change without notice Printed in Canada.